

Polarization Maintaining Low Loss Coupler Fibers



Coherent's broad line of PM fibers now includes PM980C-HP & PM14XXC-HP coupler fibers. Components designed with these new coupler fibers exhibit insertion losses up to one order of magnitude better than was previously possible. These fibers also demonstrate superior polarization control in coupler applications, resulting in increased system and network efficiencies.

Typical Applications

- Couplers and combiners
- Pump combiners
- Raman gain modules

Features & Benefits

- Dramatically reduced insertion loss — Lower system cost
- High proof test (200kpsi) — Low risk of mechanical handling failure
- High fatigue failure resistance — Longest service life

Optical Specifications

| | PM980C-HP | PM14XXC-HP |
|-----------------------|--|--|
| Operating Wavelength | 970 – 1550 nm | 1390 – 1625 nm |
| Core NA | 0.120 | 0.125 |
| Mode Field Diameter | 6.6 ± 1.0 μm @ 980 nm | 9.8 ± 0.8 μm @ 1450 nm 10.4 ± 0.8 μm @ 1550 nm |
| Cutoff | 900 ± 70 nm | 1320 ± 60 nm |
| Core Attenuation | ≤ 2.5 dB/km @ 980 nm | ≤ 1.0 dB/km @ 1450 nm ≤ 1.0 dB/km @ 1550 nm |
| Normalized Cross Talk | ≤ - 37.0 dB at 2 m @ 980 nm ≤ - 20.0 dB at 100 m @ 980 nm | ≤ - 37.0 dB at 2 m @ 1550 nm ≤ - 20.0 dB at 100 m @ 1550 nm |

Geometrical & Mechanical Specifications

| | | |
|-----------------------------|-------------------------------------|-------------------------------------|
| Cladding Diameter | 125.0 ± 1.0 μm | 125.0 ± 1.0 μm |
| Core Diameter | 5.5 μm | 8.0 μm |
| Coating Diameter | 245.0 ± 15.0 μm | 245.0 ± 15.0 μm |
| Coating Concentricity | < 5.0 μm | < 5.0 μm |
| Core/Clad Offset | ≤ 0.50 μm | ≤ 0.50 μm |
| Coating Material | Acrylate | Acrylate |
| Operating Temperature Range | -40 to 85 °C | -40 to 85 °C |
| Proof Test Level | ≥ 200 kpsi (1.4 GN/m ²) | ≥ 200 kpsi (1.4 GN/m ²) |



Nufern • 7 Airport Park Road, East Granby, CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 • Email: tech.sales@coherent.com
www.coherent.com ; www.shop.coherent.com • Coherent products are manufactured under an ISO 9001:2008 certified quality management system.



Custom developed fiber (FUD) specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Coherent can assist with your requirements.

NU0042- 11/12/2020